



How to change fuel filter on **Mercedes W204** – replacement guide

VIDEO TUTORIAL




i Important!

This replacement procedure can be used for:

MERCEDES-BENZ G-Class Off-Road (W461) G 280 CDI (461.304, 461.346, 461.370, 461.334, 461.339,...), MERCEDES-BENZ Sprinter 3.5-T Minibus (W906) 318 CDI 3.0 (906.731, 906.733, 906.735), MERCEDES-BENZ Sprinter 3.5-T Platform/Chassis (W906) 313 CDI 2.2 4x4 (906.131, 906.133, 906.135), MERCEDES-BENZ C-Class T-modell (S203) C 220 CDI (203.208), MERCEDES-BENZ Vito Mixto (W639) 122 CDI 3.0, MERCEDES-BENZ Vito Minibus (W639) 122 CDI 3.0, MERCEDES-BENZ Viano (W639) CDI 3.0 (639.811, 639.813, 639.815), MERCEDES-BENZ A-Class (W169) A 200 CDI (169.308, 169.008), MERCEDES-BENZ E-Class T-modell (S211) E 220 T CDI, MERCEDES-BENZ E-Class Saloon (W211) E 220 CDI, MERCEDES-BENZ S-Class Saloon (W221) S 350 CDI, MERCEDES-BENZ Sprinter 2-T Minibus (W901, W902) 216 CDI 2.7, MERCEDES-BENZ Sprinter 3-T Minibus (W903) 316 CDI 2.7, MERCEDES-BENZ Sprinter 2-T Van (W901, W902) 216 CDI 2.7, MERCEDES-BENZ Sprinter 2-T Platform/Chassis (W901, W902) 216 CDI 2.7, (+ 179)

The steps may slightly vary depending on the car design.

REPLACEMENT: FUEL FILTER – MERCEDES W204. LIST OF THE TOOLS YOU'LL NEED:



- All-purpose cleaning spray
- Torx bit T20
- Clic-R collar pliers
- Crow bar
- Fender cover

BUY TOOLS

Replacement: fuel filter – Mercedes W204. Tip from AUTODOC:

- Ensure adequate ventilation of the workplace. Fuel vapors are poisonous.
- Please note: all work on the car – Mercedes W204 – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:


1

Open the hood.



2

Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.



3

Remove the engine cover.



Replacement: fuel filter – Mercedes W204. Tip:

- Raise the engine cover, holding it on two sides simultaneously.
- Do not apply excessive force when removing the part. Otherwise you may damage it.


4

Clean the fasteners of the fuel supply lines. Use all-purpose cleaning spray.




5

Unplug the vacuum valve connector.




6


Detach the vacuum valve from its mounting seat and set it aside. Use a crowbar.




- 7 Detach the connector of the water-in-fuel sensor.



- 8 Loosen the fastening clamps of the fuel filter pipes. Use a crowbar.



- 9 Detach the tubes from the fuel filter.




Replacement: fuel filter – Mercedes W204. AUTODOC recommends:

- Be careful! Fuel may leak from the filter housing and hoses.


- 10 Unscrew the water-in-fuel sensor fasteners. Use Torx T20.



- 11 Disconnect the water-in-fuel sensor from the fuel filter.



- 12 Unclip the fuel filter retainer. Use a crowbar.



- 13 Remove the fuel filter.




- 14 Install a new fuel filter.



AUTODOC recommends:

- During installation, take care to prevent dust and dirt from getting into the fuel filter housing.
- Attention! Use quality filters – Mercedes W204.


- 15** Fasten the fuel filter retainer. Use a crowbar.




- 16** Install the water-in-fuel sensor.




- 17** Screw in the water-in-fuel sensor fasteners. Use Torx T20.




- 18** Attach the tubes to the fuel filter.




- 19** Tighten the fastening clamps of the fuel filter pipes. Use clic-R collar pliers.




- 20 Attach the connector of the water-in-fuel sensor.




- 21 Install the vacuum valve.



- 22 Plug in the vacuum valve connector.




- 23 Prime the fuel system.



- 24 Clean the fuel filter. Use all-purpose cleaning spray.



- 25 Run the engine for a few minutes. This is necessary in order to make sure that the component operates properly.



- 26 Shut off the engine.

Replacement: fuel filter – Mercedes W204. Tip from AUTODOC experts:

- To protect the environment from pollution, be sure to dispose of the used filters at special collection points.

- 27 Install the engine cover and secure it.




AUTODOC recommends:


- Replacement: fuel filter – Mercedes W204. Do not use excessive force during installation. This may damage the part.

28

Remove the fender protection cover.

**29**

Close the hood.

**WELL DONE!** **VIEW MORE TUTORIALS**

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR MERCEDES

FUEL FILTER: A WIDE SELECTION

CHOOSE CAR PARTS FOR MERCEDES W204

FUEL FILTER FOR MERCEDES: BUY NOW

FUEL FILTER FOR MERCEDES W204: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.